

➔ WIDE-ANGLE FRONT VIEW CAMERA:



RDC-308

FEATURES

RESOLUTION:	1080P HD
WDR:	120db (Max)
WATERPROOF:	No
WIDE VIEWING ANGLE:	170°
POWER SUPPLY:	DC 12V / DC10~32V
ANTI-VIBRATION:	ISO 16750-3 4.1.2.7: 2012
WORKING TEMPERATURE:	-20°C ~ +70°C

SPECIFICATIONS

IMAGE DEVICE:	1/2.8" CMOS
FRAME RATE:	25 fps / 30 fps
EFFECTIVE PIXELS:	1920 (H) x 1080 (V)
PIXEL SIZE:	2.9 μm x 2.9 μm
SCANNING SYSTEM:	Progressive Scanning
SYNC. SYSTEM:	Internal
RESOLUTION:	1080P
WATERPROOF RATING:	Non Waterproof
VIEWING ANGLE:	170° / 130° / 110° / 100° / 65°
MICROPHONE/AUDIO:	Yes
MIINIMUM ILLUMINATION:	0.1 Lux
WDR:	120db
IMAGE MODE:	Normal
VIDEO OUTPUT:	1.0Vp-p, 75Ohm
GAMMA CONSUMPTION:	0.45
AGC:	Auto
WHITE BALANCE:	Auto
ELECTRONIC SHUTTER:	1/30 (1/25)~1/50,000 Seconds
BLC:	Auto
OPERATING TEMPERATURE:	-20°C ~ 70°C, RH 95% MAX.
STORAGE TEMPERATURE:	-30°C ~ 80°C, RH 95% MAX.

Revised: June 2020